# **Configuration Cable CONFCAB**

# **Configuration kit for ABL charging stations**

The CONFCAB configuration cable connects ABL charging stations with a free USB port on a computer. Using various software applications provided by ABL, the computer can then be used to prepare Controller and Extender charging stations for deployment in group installations or standalone operations respectively. The CONFCAB kit contains all cables and adapters required to connect with all bus interfaces in the ABL charging stations eMH1, eMH2, eMH3, eMC2 and eMC3 as well as in the external control units 1V0001 and 1V0002.



#### **General information**

Model	Configuration kit for the ABL charging stations eMH1, eMH2, eMH3, eMC2 and eMC3 as well as for the external control units 1V0001 and 1V0002.
Product number	CONFCAB
EAN number	4011721183374
Commodity code	85423190
Packaging unit (PU)	1 unit
Packaging dimensions (H×W×D)	85 × 120 × 120 mm
Weight	186 g
Items supplied	USB extension cable, USB to RJ45 adapter, RJ45 to individual strands patch cable, RJ45 to RJ45 patch cable, RJ45 to RJ12 patch cable, download information card

## **Supported interfaces**

Interface for ABL charging stations with multipoint connector	Type A USB plug to 6 individual strands (incl. end ferrules)
Interface for ABL charging stations with RJ45 socket	Type A USB plug to RJ45 plug
Interface for ABL charging stations with RJ12 socket	Type A USB plug to RJ12 plug

### **Product information**

Patch cable length	1.50 m each
Patch cable composition	All are S/FTP cables (Screened Foiled Twisted Pair)
Patch cable category	CAT 6 each
PIN allocation for RJ45 to RJ45 patch cable	1:1 wired / straight

# **Technical data / operating environment**

Rated voltage	5 V <sub>DC</sub>
Ambient temperature (storage)	-30 to 85°C
Operating temperature	-30 to 60°C
Relative humidity	5 to 95%, no condensation
Class of protection	IP20

## Standards / directives

RoHS Guideline	2011/65/EU
EMC Guideline	2014/30/EU

Subject to change: All performance characteristics, technical and other specifications are subject to change without prior notice.